


MOD.NS2 Moduł nasadek uderowych 1/2" 6-kątnych metrycznych



- Zawiera:
 - NS.A 13 - 14 - 15 - 16 - 17 - 18 - 19 - 21 - 22 - 24 - 27 - 30 - 32: Nasadki uderowe 1/2" krótkie.
 - NS.236A i NS.237A: Nasadki uderowe 1/2" z uchwytem do końcówek.
 - Końcówki uderowe: ENH.3 6 - 7 - 8 - 10 - 12 - 14 ; ENP.2 2 - 3 - 4 ; NEX.A 30 - 40 - 45 - 50 - 55.
 - Wkładka termoformowana: PL.623.
- Masa: 985 g.

Nasadki i akcesoria uderowe 1/2"

NS.A - Nasadki uderowe 1/2" 6-kątne metryczne




NF ISO 2725-2, NF ISO 1711-2, ISO 2725-2, ISO 1711-2, DIN 3129, ASME B107.33

- Dla Państwa bezpieczeństwa należy zawsze używać nasadek uderowych z odpowiednimi pierścieniami i kółkami zabezpieczającymi.

	A [mm]	⌀ [mm]	d [mm]	d1 [mm]	GA	BA	L [mm]	L1 [mm]	ΔΔ [g]
NS.8A	8	6	25	15,0	GA.20A	BA.20A	38	9	70
NS.9A	9	6	25	16,0	GA.20A	BA.20A	38	12	70
NS.10A	10	6	25	17,5	GA.20A	BA.20A	38	12	75
NS.11A	11	6	25	18,7	GA.20A	BA.20A	38	12	76
NS.12A	12	6	25	20,0	GA.20A	BA.20A	38	12	75
NS.13A	13	6	25	21,0	GA.20A	BA.20A	38	12	76
NS.14A	14	6	25	22,5	GA.20A	BA.20A	38	12	83
NS.15A	15	6	30	23,7	GA.24A	BA.25A	38	12	112
NS.16A	16	6	30	25,0	GA.24A	BA.25A	38	12	105
NS.17A	17	6	30	26,5	GA.24A	BA.25A	38	13	112
NS.18A	18	6	30	27,5	GA.24A	BA.25A	38	13	110
NS.19A	19	6	30	29,0	GA.24A	BA.25A	38	14	112
NS.20A	20	6	30	30,0	GA.24A	BA.25A	38	15	116
NS.21A	21	6	30	31,0	GA.24A	BA.25A	38	15	156
NS.22A	22	6	30	32,5	GA.24A	BA.25A	38	16	156
NS.23A	23	6	30	33,5	GA.24A	BA.25A	38	16	156
NS.24A	24	6	30	35,0	GA.24A	BA.25A	45	20	169
NS.26A	26	6	30	38,0	GA.24A	BA.25A	50	24	192
NS.27A	27	6	30	39,0	GA.24A	BA.25A	50	24	220
NS.28A	28	6	30	40,0	GA.24A	BA.25A	50	24	273
NS.29A	29	6	30	41,0	GA.24A	BA.25A	50	24	276
NS.30A	30	6	30	43,0	GA.24A	BA.25A	50	24	285
NS.32A	32	6	30	45,0	GA.24A	BA.25A	50	24	278

NS.A - Nasadki uderowe 1/2" 6-kątne calowe



ASME B107.2

- Dla Państwa bezpieczeństwa należy zawsze używać nasadek uderowych z odpowiednimi pierścieniami i kółkami zabezpieczającymi.

	A ["]	⌀ [mm]	d [mm]	d1 [mm]	GA	BA	L [mm]	L1 [mm]	ΔΔ [g]
NS.3/8A	3/8	6	25	17,5	GA.20A	BA.20A	38	12	75
NS.7/16A	7/16	6	25	18,7	GA.20A	BA.20A	38	12	76
NS.1/2A	1/2	6	25	21,0	GA.20A	BA.20A	38	12	76
NS.9/16A	9/16	6	25	22,5	GA.20A	BA.20A	38	12	83
NS.5/8A	5/8	6	30	25,0	GA.24A	BA.25A	38	12	105
NS.11/16A	11/16	6	30	26,5	GA.24A	BA.25A	38	13	112
NS.3/4A	3/4	6	30	29,0	GA.24A	BA.25A	38	14	112
NS.13/16A	13/16	6	30	31,0	GA.24A	BA.25A	38	15	156
NS.7/8A	7/8	6	30	33,5	GA.24A	BA.25A	38	16	162
NS.15/16A	15/16	6	30	33,5	GA.24A	BA.25A	38	16	162
NS.1'A	1'	6	30	38,0	GA.24A	BA.25A	50	24	192
NS.1'1/16A	1' 1/16	6	30	39,0	GA.24A	BA.25A	50	24	220